Bow Top

PRODUCT INFORMATION

Allowing for steps of
0-16mm & 56-72mm

Standard Bow Top

Bow Top Specification Guidelines (BS 1722 Pt. 9)

PANELS

Heights	Up to 2000mm (900*, 1000*, 1200* & 1800mm*)
Bar Diameter	12, 16 or 20mm according to height
Bar Centres	12 & 16mm @ 112mm ctrs / 20mm @ 120mm ctrs
Panel Width	2720mm

*Held in Stock

POSTS

Post Size	Up to 1200mm – 50 x 50 SHS Over 1600mm – 102 x 44 RSJ (or box section alternative)
Post Centres	50 x 50 SHS 2800mm 102 x 44 RSJ 2750mm

Blythe Bow Top

Hollington Bow Top

Tittesworth Bow Top

Interlaced Bow Top

Features:

- Compliant with BS 1722 Pt. 9
- Various heights available from stock
- Stepping cleats
- Security fixings
- Range of standard feature designs available
- Hot Dip Galvanised to BS EN ISO 1461
- Polyester Powder Coating (optional)

Suitable for:

- Schools, Colleges & Universities
- Housing Estates
- Retail Parks
- Parks and Open Spaces

Caloo Ltd,
Unit 9A, Triangle Business Park,
Wendover Road,
Stoke Mandeville,
Buckinghamshire,
HP22 5BL

01296 614448
info@caloo.co.uk