



Championship Fencing

Description:

A combination of steel rebound fence specifications offering good ball rebound and fence strength by featuring 8mm twin horizontal and 6mm vertical bars with 50mm x 60mm aperture to 1.2m lower section (1m for 1m high) and 50mm x 200mm aperture to remainder of full height. Galvanised and Powder Coated available in your choice of colour. Rectangular fence posts and flush panel fixing for excellent ball rebound. Goals and gates to match fencing.

Suitability:

Suitable for installation into sites which demand the a good level of rebound, durability and performance but require an attractive design to create a practical feature which will require little regular maintenance.





Championship Fencing

Fence Panels:

- Panel: 2510mm wide
- 50mm x 200mm mesh with 6mm vertical wires at 50mm centres and dual 8mm horizontal wires at 200mm centres,
- 'Super strength' mesh to the bottom 1m - 1.2m comprising additional dual horizontal wires to create a tighter mesh size of 50mm x 67mm,
- Integral heavy use basketball hoop and 19mm thick HDPE backboard, available on request,
- Integral goal recesses of approximately 3m wide x 2m high x 1.2m deep, available on request.

Posts:

- 80mm x 40mm RHS with fixings at 200mm centres,

Anti Corrosion / Paint Finish Posts:

Galvanised to BS729 and electrostatic Powder coating application of Lead Free paint to average DFT of 80-100 microns.

Anti Corrosion / Paint Finish Rebound Panels:

Galvanised to BS729 and electrostatic Powder coating application of Lead Free paint to average DFT of 80-100 microns.

Additional Items:

- Single leaf gate - 1.2m wide x variable heights, complete with necessary gate posts, slam plate including rubber bump stop and holed slide latch (mid panel gate to cut into panel).

Installation:

- Set out and erect fencing: As shown on drawings.
- Gradients:

In the event of installing on a gradient, to assist with drainage, post must be erected vertically and panels can be stepped approximately 35mm maximum by suspending the top horizontal on the second clip from the top of the post. Steeper slopes will require extra-long posts, manufactured with additional clips and threaded inserts. With posts set rigid, plumb and to specified depth, or greater where necessary to ensure adequate support.

Sizes:

Fencing heights range from 1 - 5 metres tall.

Civil Engineering:

Wide variety of surfaces and line marking available on request.

