

PRODUCT DATASHEET

SWING ST1421





Device Specifications		Minimal space		
Safety zone	12,95 m ²	_	7,40	
Length	2,48 m	•	.,	
Width	1,94 m	_	1,94	
Total height	2,33 m			
Free fall height	1,30 m	_		
Age range	1-3/3-14 years	- ; 		
In accordance w/ EN standards	1176-1:2017		Ī	
Weight of the heaviest part [kg]	15		î l	
Dimension of the biggest part [cm]	300x8x8		T	C
Availability of spare parts	Yes	┨└────		

Material Specification

- Galvanized and/or powder coated steel 80 x 80 mm construction;
- Top of the construction is secured with rubber caps;
- Stainless steel screws or screws covered with plastic caps;
- No sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- Durable certified, safe seat;

Additional comments

- The equipment is certified by an accrediting organization or by certificate of conformity;
- Depth of foundations on a flat surface: 80/70/60 cm;
- The equipment is designed for public playgrounds; The equipment render is of an illustrative nature and shows only the general specification of the equipment, but not its actual appearance. The colours may differ from those demonstrated on render.
- Available with different seat options: R1 flat seat, R2 cradle seat, R3 belt seat, R5 flat with back rest;

Surfaces

Due to the free fall height of the equipment, the EN 1176-1:2017 standard allows the following surfaces: sand with minimal layer thickness of 30 cm (A,C), synthetic material approved for free fall of 1,30 m (A,B,C)