

PRODUCT DATASHEET


minisweet 0110

PLAYGROUND FOUIPMEN

STAINLESS STEEL DEVICE

Device Specifications			
Safety zone	28,10 m ²		
Length	2,46 m		
Width	2,53 m		
Total height	2,50 m		
Free fall height	0,90 m		
Age range	1-8 yrs		
In accordance w/ EN standards	1176-1:2009		
Availability of spare parts	Yes		
Weight of the heaviest part [kg]	15		
Dimension of the biggest part [cm]	63x232x60		

Minimal space





MATERIAL SPECIFICATION

Minisweet series - playground devices for the youngest children, equipped with a variety of educational elements and handling panels that stimulate the imagination, exercise manual abilities and boost the development of motor and cognitive skills through fun activities.

- Stainless steel construction
- · Roofs, shields, educational panels made out of atmospheric condition resistant HDPE polythene plates
- · All screws covered with colorful plastic caps
- · Platforms made out of anti-skidding plywood or HPL plate

EDUCATION AND DEVELOPMENT

- · Mini shop: panel with digits and mathematical characters
- Abacus: geometric figures
- Panel: sea animals
- · Flower: handling elements

ADDITIONAL COMMENTS

- The device is certified by an accrediting organization or declaration of conformity
- Embedded 76/65/55 cm deep in flat ground
- The device is designed for public playgrounds
- The slide should not be positioned in a southbound direction

Due to the free fall height of the device, the EN 1176-1:2009 standard allows the following surfaces to cushion a fall. The level of granular materials requires filling in, conservation of synthetic materials is required in accordance with the manufacturer's instructions. Dimensions of the foundation are described in installation instruction.

louridation are described in installation instruction.				
Material	Description [mm]	Minimal layer thickness [mm]	Dimensions foundation	
Turf/Soil			A,B,C	
Tree bark	Grain size from 20 to 80	300	A,C	
Chip	Grain size from 5 to 30	300	A,C	
Sand	Grain size from 0,2 to 2	300	A,C	
Gravel	Grain size from 2 to 8	300	A,C	
Synthetic materials	Free fall approval		A,B,C	