


# **PRODUCT DATASHEET**

## FIRE TRUCK SPRING RIDER



| Device Specifications           |                      |
|---------------------------------|----------------------|
| Safety zone                     | 11,05 m <sup>2</sup> |
| Length                          | 0,78 m               |
| Width                           | 0,43 m               |
| Total height                    | 0,82 m               |
| Free fall height                | < 0,60 m             |
| Age range                       | 1-12 years           |
| In accordance w PN-EN standards | 1176-1:2017          |
| Availability of spare parts     | Yes                  |



### MATERIAL SPECIFICATION

- Steel spring 20 mm, iron phosphorated and powder coated;
- Covers and seats made of weather-resistant HDPE polyethylene plates;
- Backrest made of waterproof HPL;
- · Stainless steel and / or galvanized screws covered with plastic caps;
- Other metal elements, galvanized and / or powder coated;
- Stainless steel bars;

#### **ADDITIONAL COMMENTS**

- Depth of foundations on a flat surface 40/5 cm;
- No sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- The equipment is designed for public playgrounds;

• The equipment render is of an illustrative nature and shows only the general specification of the equipment, but not actual appearance;

### SURFACES

Due to the free fall height of the equipment, the PN-EN 1176-1:2017 standard allows the following surfaces: turf/ soil (A,B,C), sand with minimal layer thickness of 30 cm (A,C), synthetic material approved for free fall of 0,60 m (A,B,C).