


SPRING 0653 KANGAROO SPRING RIDER



<b>Device Specifications</b>	
Safety zone	10,00 m <sup>2</sup>
Length	0,72 m
Width	0,22 m
Total height	0,80 m
Free fall height	< 0,60 m
Age range	1-12 years
In accordance w PN-EN standards	1176-1:2017



## **MATERIAL SPECIFICATION**

- Steel spring 20 mm, iron phosphorated and powder coated;
- Covers and seats made of weather-resistant HDPE polyethylene plates;
- Stainless steel and / or galvanized screws covered with plastic caps;
- Other metal elements, galvanized and / or powder coated;
- Ergonomic handles and footrests made of durable material;

## **ADDITIONAL COMMENTS**

- Depth of foundations on a flat surface 40/5 cm;
- No sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- The equipment is designed for public playgrounds;
- The equipment render is of an illustrative nature and shows only the general specification of the equipment, but not actual appearance;

## **SURFACES**

Due to the free fall height of the equipment, the PN-EN 1176-1:2017 standard allows the following surfaces: turf/ soil (A,B,C), sand with minimal layer thickness of 30 cm (A,C), synthetic material approved for free fall of 0,60 m (A,B,C).