
PRODUCT DATASHEET

SOLO 1720 SOLO EQUIPMENT



| Device Specifications | |
|---------------------------------|----------------------|
| Safety zone | 16,20 m ² |
| Length | 2,40 m |
| Width | 0,77 m |
| Total height | 2,06 m |
| Free fall height | <0,60 m |
| Age group | 1-8 years |
| In accordance w PN-EN standards | 1176-1:2017 |
| Availability of spare parts | Yes |



MATERIAL SPECIFICATION

- Stainless steel or Galvanized and/or powder coated steel 80x80 mm construction;
- Top od the construction is secured with rubber caps;
- Roofs and panels are made of atmospheric condition resistant HDPE plates;
- Screws covered with plastic caps or made of stainless steel;
- Calibrated chain, preventing fingers from getting trapped;
- Xylophone made of aluminum pipes;

ADDITIONAL COMMENTS

- Depth of foundations on a flat surface 80/70/60 cm;
- No sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- The equipment is designed for public playgrounds;
- The equipment render is of an illustrative nature and shows only the general specification of the equipment, but not actual appearance;
- The equipment is suitable for people with disabilities;

SURFACES

Due to the free fall height of the equipment, the PN-EN 1176-1:2017 standard allows the following surfaces: turf/ soil (A,B,C), sand with minimal layer thickness of 30 cm (A,C), synthetic material approved for free fall of 0,60 m (A,B,C).